

View Online at <https://aerobasegroup.com/nsn/4320-00-125-4359>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Base

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Round flange

Discharge Connection Quantity:

1

Discharge Connection Type:

Round flange

Current Type:

Ac

Media For Which Designed:

Water, salt

Pump Quantity:

1

Cooling Method:

Blower cooled

Maximum Discharge Flow Rate:

800.0 gallons per minute

Total Head:

125.000 feet

Operating Speed At Rated Capacity:

3600.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Design:

Radial flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Double

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Features Provided:

Self-priming

Prime Mover Power Rating:

100.000 horsepower

Voltage In Volts:

440.0

Phase:

Three

Frequency In Hertz:

60.0

Specification Or Standard:

C2 class

Reference Number Differentiating Characteristics:

As differentiated by w/reliance electric motor, dwg no. 85799-51

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400