

View Online at <https://aerobasegroup.com/nsn/4320-00-131-6554>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Mounting Type:**

Base

**Stage Quantity:**

1

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Round flange

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Round flange

**Current Type:**

Ac

**Media For Which Designed:**

Water, salt

**Pump Quantity:**

1

**Cooling Method:**

Blower cooled

**Maximum Discharge Flow Rate:**

350.0 gallons per minute

**Total Head:**

336.000 feet

**Operating Speed At Rated Capacity:**

3600.0 revolutions per minute

**Pumping Element Operating Position:**

Horizontal

**Centrifugal Pump Design:**

Radial flow

**Centrifugal Pump Impeller Quantity:**

1

**Centrifugal Pump Impeller Suction Type:**

Double

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Features Provided:**

Self-priming

**Prime Mover Power Rating:**

60.000 horsepower

**Voltage In Volts:**

440.0

**Phase:**

Three

**Frequency In Hertz:**

60.0

**Specification Or Standard:**

C2 class

**Reference Number Differentiating Characteristics:**

As differentiated by w/reliance electric motor, dwg no. 87569

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A19400