NSN 4320-00-132-5248

Centrifugal Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-132-5248

| Prime Mover Quantity: | | | | |
|---|--|--|--|--|
| 1 | | | | |
| Stage Quantity: | | | | |
| 1 | | | | |
| Intake Connection Quantity: | | | | |
| 1 | | | | |
| Intake Connection Type: | | | | |
| Round flange | | | | |
| Discharge Connection Quantity: | | | | |
| 1 | | | | |
| Discharge Connection Type: | | | | |
| Round flange | | | | |
| Current Type: | | | | |
| Dc | | | | |
| Media For Which Designed: | | | | |
| Water, salt | | | | |
| Environmental Protection: | | | | |
| Dripproof | | | | |
| Pump Quantity: | | | | |
| 1 | | | | |
| Maximum Discharge Flow Rate: | | | | |
| 325.0 gallons per minute | | | | |
| Total Head: | | | | |
| 25.000 feet | | | | |
| Operating Speed At Rated Capacity: | | | | |
| 1750.0 revolutions per minute | | | | |
| Pumping Element Operating Position: | | | | |
| Horizontal | | | | |
| Centrifugal Pump Design: | | | | |
| Radial flow | | | | |
| Centrifugal Pump Impeller Quantity: | | | | |
| 1 | | | | |
| Centrifugal Pump Impeller Suction Type: | | | | |
| Single | | | | |
| Prime Mover Type: | | | | |
| Electric motor | | | | |
| Inclosure Type: | | | | |
| Partially enclosed | | | | |
| Prime Mover Power Rating: | | | | |
| 3.670 horsepower | | | | |
| Voltage In Volts: | | | | |
| 250.0 | | | | |

NSN 4320-00-132-5248

Centrifugal Pump Unit - Page 2 of 2



| Reference | Number | Differentiating | Characteristics |
|-----------|--------|-----------------|-----------------|
| | | | |

As differentiated by cw pump shaft rotation

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400