

View Online at <https://aerobasegroup.com/nsn/4320-00-137-7141>

Prime Mover Quantity:

1

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Threaded external

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded external

Current Type:

Ac

Media For Which Designed:

Water, fresh

Environmental Protection:

Waterproof

Pump Quantity:

1

Maximum Discharge Flow Rate:

3.0 gallons per minute

Discharge Pressure:

2.0 pounds per square inch gage

Total Head:

4.600 feet

Operating Speed At Rated Capacity:

3200.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Design:

Mixed flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Unpackaged Unit Length:

3.625 inches

Unpackaged Unit Width:

3.0000 inches

Unpackaged Unit Height:

3.625 inches

Pump Basic Material:

Plastic

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

0.5

Discharge Connection Thread Size And Series/type Designator:

0.250-18 npt

Intake Connection Thread Size And Series/type Designator:

0.250-18 npt

Features Provided:

Self-priming

Prime Mover Power Rating:

0.005 horsepower

Voltage In Volts:

115.0

Phase:

Single

Frequency In Hertz:

50.0 and 60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400