

View Online at <https://aerobasegroup.com/nsn/4320-00-137-9690>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Water, fresh

Mounting Type:

Wheel

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Round flange

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Media For Which Designed:

Water, fresh

Pump Quantity:

1

Total Head:

60.000 feet

Suction Lift:

10.000 feet

Operating Speed At Rated Capacity:

2400.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Design:

Radial flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Operation Relationship Design:

Simultaneous

Prime Mover Type:

Diesel engine

Discharge Connection Thread Size And Series/type Designator:

6.000-8 npt

Features Provided:

Self-priming

Prime Mover Power Rating:

50.000 horsepower

Special Features:

1000 min gpm pump capacity, trash type pump impeller, capable of handling 3 in. Solids, furnished w/5 suction hoses w/smooth bore 6 in. By 10 ft lg ea w/npt swivel type pin lug male and female, hose rack, 2 grooved 6 in. Npt adapter nipples, 2 grooved 6 in. Npt straight end adapters, 2 grooved 6 in. Npt couplers, ft strainer valve, metal tool box, w/hr meter, tie down devices

Specification Or Standard:

1 type and 90m size and aterial a weight and 4 class and b style

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400