

View Online at <https://aerobasegroup.com/nsn/4320-00-139-5182>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Stage Quantity:**

1

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Threaded internal

**Current Type:**

Ac

**Media For Which Designed:**

Oil

**Environmental Protection:**

Dripproof

**Pump Quantity:**

1

**Cooling Method:**

Self ventilated

**Maximum Discharge Flow Rate:**

21.5 gallons per minute

**Operating Speed At Rated Capacity:**

3450.0 revolutions per minute

**Pumping Element Operating Position:**

Vertical

**Centrifugal Pump Design:**

Mixed flow

**Centrifugal Pump Impeller Quantity:**

1

**Centrifugal Pump Impeller Suction Type:**

Double

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Open

**Discharge Connection Thread Size And Series/type Designator:**

0.500-14 npt

**Features Provided:**

Self-priming

**Prime Mover Power Rating:**

0.100 horsepower

**Voltage In Volts:**

115.0 and 230.0 and 230.0 and 460.0

**Phase:**

Single and three

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiiig:**

A19400