NSN 4320-00-140-4273

Centrifugal Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-140-4273

| Prime Mover Quantity: |
|---|
| 1 |
| Prime Mover Cooling Medium: |
| Air |
| Mounting Type: |
| Base |
| Stage Quantity: |
| 1 |
| Intake Connection Quantity: |
| 1 |
| Discharge Connection Quantity: |
| 1 |
| Discharge Connection Type: |
| Round flange |
| Current Type: |
| Ac |
| Media For Which Designed: |
| Water, fresh |
| Environmental Protection: |
| Dripproof |
| Pump Quantity: |
| 1 |
| Maximum Discharge Flow Rate: |
| 20.0 gallons per minute |
| Discharge Pressure: |
| 50.0 pounds per square inch gage |
| Operating Speed At Rated Capacity: |
| 3600.0 revolutions per minute |
| Pumping Element Operating Position: |
| Vertical |
| Centrifugal Pump Design: |
| Radial flow |
| Centrifugal Pump Impeller Quantity: |
| 1 |
| Centrifugal Pump Impeller Suction Type: |
| Single |
| Unpackaged Unit Length: |
| 16.100 inches |
| Unpackaged Unit Width: |
| 16.1000 inches |
| Unpackaged Unit Height: |
| 54.900 inches |

NSN 4320-00-140-4273Centrifugal Pump Unit - Page 2 of 2



| Prime Mover Type: |
|---------------------------|
| Electric motor |
| Inclosure Type: |
| Fully enclosed |
| Prime Mover Power Rating: |
| 3.000 horsepower |
| Voltage In Volts: |
| 440.0 |
| Phase: |
| Three |
| Frequency In Hertz: |
| 60.0 |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A19400