## NSN 4320-00-142-1692

Centrifugal Pump Unit - Page 1 of 2

**Prime Mover Quantity:** 



View Online at https://aerobasegroup.com/nsn/4320-00-142-1692

Prime Mover Cooling Medium:
Air
Mounting Type:
Base
Stage Quantity:
1
Intake Connection Quantity:
1
Intake Connection Type:
Threaded internal
Discharge Connection Quantity:
1
Discharge Connection Type:
Threaded internal
Current Type:
Dc
Media For Which Designed:
Water, fresh
Environmental Protection:
Splashtight
Pump Quantity:
1
Cooling Method:
Blower cooled
Maximum Discharge Flow Rate:
21.5 gallons per minute
Total Head:
112.000 feet
Suction Lift:
15.000 feet
Operating Speed At Rated Capacity:
1750.0 revolutions per minute
Pumping Element Operating Position:
Horizontal
Centrifugal Pump Design:
Radial flow
Centrifugal Pump Impeller Quantity:
1
Centrifugal Pump Impeller Suction Type:
Single

## **NSN 4320-00-142-1692**Centrifugal Pump Unit - Page 2 of 2



Prime Mover Type:
Electric motor
Inclosure Type:
Fully enclosed
Current Rating In Amps:
15.8
Discharge Connection Thread Size And Series/type Designator:
1.250-11-1/2 npt
Intake Connection Thread Size And Series/type Designator:
1.500-11-1/2 npt
Features Provided:
Self-priming
Voltage In Volts:
115.0
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A40400