

View Online at <https://aerobasegroup.com/nsn/4320-00-142-1734>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Dc

Media For Which Designed:

Water, fresh or water, salt

Environmental Protection:

Splash proof

Pump Quantity:

1

Cooling Method:

Blower cooled

Maximum Discharge Flow Rate:

5.0 gallons per minute

Total Head:

90.000 feet

Suction Lift:

15.000 feet

Operating Speed At Rated Capacity:

1750.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Design:

Radial flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

3.0

Discharge Connection Thread Size And Series/type Designator:

1.000-11-1/2 npt

Intake Connection Thread Size And Series/type Designator:

1.250-11-1/2 npt

Features Provided:

Self-priming

Prime Mover Power Rating:

0.333 horsepower

Voltage In Volts:

115.0

Reference Number Differentiating Characteristics:

As differentiated by pacs ahyv and ahyx

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400