

View Online at <https://aerobasegroup.com/nsn/4320-00-149-7521>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Base

Stage Quantity:

2

Intake Connection Quantity:

1

Intake Connection Type:

Round flange

Discharge Connection Quantity:

1

Discharge Connection Type:

Round flange

Current Type:

Ac

Media For Which Designed:

Water, fresh

Pump Quantity:

1

Cooling Method:

Self ventilated

Maximum Discharge Flow Rate:

60.0 gallons per minute

Discharge Pressure:

70.0 pounds per square inch gage

Total Head:

144.000 feet

Operating Speed At Rated Capacity:

3550.0 revolutions per minute

Pumping Element Operating Position:

Vertical

Centrifugal Pump Design:

Radial flow

Centrifugal Pump Impeller Quantity:

2

Centrifugal Pump Impeller Suction Type:

Single

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

9.3

Features Provided:

Self-priming

Voltage In Volts:

440.0

Phase:

Three

Frequency In Hertz:

60.0

Reference Number Differentiating Characteristics:

As differentiated by reliance electric co motor dwg no. 87286 and cutler-hammer controller dwg no. 6962h102

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400