

View Online at <https://aerobasegroup.com/nsn/4320-00-150-6201>

Prime Mover Quantity:

1

Mounting Type:

Base

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Ac

Media For Which Designed:

Water, fresh

Pump Quantity:

1

Maximum Discharge Flow Rate:

20.0 gallons per minute

Operating Speed At Rated Capacity:

3450.0 revolutions per minute

Pumping Element Operating Position:

Vertical

Centrifugal Pump Design:

Mixed flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

8.0

Discharge Connection Thread Size And Series/type Designator:

1.250-11-1/2 npt

Intake Connection Thread Size And Series/type Designator:

1.500-11-1/2 npt

Features Provided:

Self-priming

Prime Mover Power Rating:

0.750 horsepower

Voltage In Volts:

115.0

Phase:

Single

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400