

View Online at <https://aerobasegroup.com/nsn/4320-00-161-2961>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Stage Quantity:**

1

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Round flange

**Current Type:**

Ac

**Media For Which Designed:**

Water, fresh

**Environmental Protection:**

Splash proof

**Pump Quantity:**

1

**Maximum Discharge Flow Rate:**

25.0 gallons per minute

**Total Head:**

70.000 feet

**Operating Speed At Rated Capacity:**

1740.0 revolutions per minute

**Pumping Element Operating Position:**

Horizontal

**Centrifugal Pump Design:**

Radial flow

**Centrifugal Pump Impeller Quantity:**

1

**Centrifugal Pump Impeller Suction Type:**

Single

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Prime Mover Power Rating:**

2.000 horsepower

**Voltage In Volts:**

440.0

**Phase:**

Three

**Special Features:**

Submerged impeller, with integral strainer

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A19400