

View Online at <https://aerobasegroup.com/nsn/4320-00-165-5005>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Water, fresh

Stage Quantity:

1

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Ac

Media For Which Designed:

Water, fresh

Environmental Protection:

Submersible

Pump Quantity:

1

Maximum Discharge Flow Rate:

30.0 gallons per minute

Discharge Pressure:

40.0 pounds per square inch gage

Suction Lift:

40.000 feet

Operating Speed At Rated Capacity:

3450.0 revolutions per minute

Pumping Element Operating Position:

Vertical

Centrifugal Pump Design:

Axial flow

Centrifugal Pump Impeller Suction Type:

Single

Operation Relationship Design:

Simultaneous

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Discharge Connection Thread Size And Series/type Designator:

2.000-11-1/2 npt

Features Provided:

Self-priming

Prime Mover Power Rating:

1.500 horsepower

Voltage In Volts:

230.0

Phase:

Three

Special Features:

Submersible with integral strainer

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400