NSN 4320-00-171-2880

Centrifugal Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-171-2880

Prime Mover Quantity:			
1			
Mounting Type:			
Base			
Stage Quantity:			
1			
Exhaust Pressure:			
15.0 pounds per square inch gage			
Intake Connection Quantity:			
1			
Intake Connection Type:			
Round flange			
Discharge Connection Quantity:			
1			
Discharge Connection Type:			
Round flange			
Media For Which Designed:			
Water, salt			
Power Drive Operating Pressure:			
540.0 pounds per square inch gage			
Pump Quantity:			
1			
Maximum Discharge Flow Rate:			
1000.0 gallons per minute			
Discharge Pressure:			
150.0 pounds per square inch gage			
Operating Speed At Rated Capacity:			
3550.0 revolutions per minute			
Pumping Element Operating Position:			
Horizontal			
Centrifugal Pump Design:			
Radial flow			
Centrifugal Pump Impeller Quantity:			
1			
Centrifugal Pump Impeller Suction Type: Double			
Volume Control Type:			
Rotary			
Control Location:			
Center			
Prime Mover Type:			
Steam turbine			

NSN 4320-00-171-2880

Centrifugal Pump Unit - Page 2 of 2



Prime Mo	over Po	ower Ra	ating:
----------	---------	---------	--------

110.000 horsepower

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400