
## NSN 4320-00-171-2880

Centrifugal Pump Unit - Page 1 of 2

**Prime Mover Quantity:** 

1

1





Mounting Type: Base **Stage Quantity:** 1 **Exhaust Pressure:** 15.0 pounds per square inch gage Intake Connection Quantity: 1 Intake Connection Type: Round flange **Discharge Connection Quantity:** 1 **Discharge Connection Type:** Round flange Media For Which Designed: Water, salt **Power Drive Operating Pressure:** 540.0 pounds per square inch gage **Pump Quantity:** 1 Maximum Discharge Flow Rate: 1000.0 gallons per minute **Discharge Pressure:** 150.0 pounds per square inch gage **Operating Speed At Rated Capacity:** 3550.0 revolutions per minute **Pumping Element Operating Position:** Horizontal **Centrifugal Pump Design:** Radial flow **Centrifugal Pump Impeller Quantity: Centrifugal Pump Impeller Suction Type:** Double **Volume Control Type:** Rotary **Control Location:** Center Prime Mover Type: Steam turbine

## NSN 4320-00-171-2880

Centrifugal Pump Unit - Page 2 of 2



## Prime Mover Power Rating:

110.000 horsepower

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A19400