NSN 4320-00-177-8453

Rotary Pump - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4320-00-177-8453

Intake Connection Quantity:
1
Intake Connection Type:
Triangular flange
Discharge Connection Quantity:
1
Discharge Connection Type:
Triangular flange
Drive Connection Type:
Multistrand v-belt
Media For Which Designed:
Hydrocarbon fuels and oils
Maximum Discharge Flow Rate:
32.8 gallons per minute
Discharge Pressure:
2500.0 pounds per square inch gage
Operating Speed At Rated Capacity:
2750.0 revolutions per minute
Pumping Element Operating Position:
Horizontal
Pump Rotation Direction:
Pump Rotation Direction: Counterclockwise
·
Counterclockwise
Counterclockwise Rotary Pump Design:
Counterclockwise Rotary Pump Design: Vane
Counterclockwise Rotary Pump Design: Vane Operation Method:
Counterclockwise Rotary Pump Design: Vane Operation Method: Powered
Counterclockwise Rotary Pump Design: Vane Operation Method: Powered Drive Shaft Type:
Counterclockwise Rotary Pump Design: Vane Operation Method: Powered Drive Shaft Type: Machine keyway
Counterclockwise Rotary Pump Design: Vane Operation Method: Powered Drive Shaft Type: Machine keyway Drive Shaft End Diameter:
Counterclockwise Rotary Pump Design: Vane Operation Method: Powered Drive Shaft Type: Machine keyway Drive Shaft End Diameter: Between 0.874 inches and 0.875 inches
Counterclockwise Rotary Pump Design: Vane Operation Method: Powered Drive Shaft Type: Machine keyway Drive Shaft End Diameter: Between 0.874 inches and 0.875 inches Drive Shaft Length:
Counterclockwise Rotary Pump Design: Vane Operation Method: Powered Drive Shaft Type: Machine keyway Drive Shaft End Diameter: Between 0.874 inches and 0.875 inches Drive Shaft Length: Between 2.155 inches and 2.165 inches
Counterclockwise Rotary Pump Design: Vane Operation Method: Powered Drive Shaft Type: Machine keyway Drive Shaft End Diameter: Between 0.874 inches and 0.875 inches Drive Shaft Length: Between 2.155 inches and 2.165 inches Shelf Life:
Counterclockwise Rotary Pump Design: Vane Operation Method: Powered Drive Shaft Type: Machine keyway Drive Shaft End Diameter: Between 0.874 inches and 0.875 inches Drive Shaft Length: Between 2.155 inches and 2.165 inches Shelf Life: N/a
Counterclockwise Rotary Pump Design: Vane Operation Method: Powered Drive Shaft Type: Machine keyway Drive Shaft End Diameter: Between 0.874 inches and 0.875 inches Drive Shaft Length: Between 2.155 inches and 2.165 inches Shelf Life: N/a Unit Of Measure:
Counterclockwise Rotary Pump Design: Vane Operation Method: Powered Drive Shaft Type: Machine keyway Drive Shaft End Diameter: Between 0.874 inches and 0.875 inches Drive Shaft Length: Between 2.155 inches and 2.165 inches Shelf Life: N/a Unit Of Measure:
Counterclockwise Rotary Pump Design: Vane Operation Method: Powered Drive Shaft Type: Machine keyway Drive Shaft End Diameter: Between 0.874 inches and 0.875 inches Drive Shaft Length: Between 2.155 inches and 2.165 inches Shelf Life: N/a Unit Of Measure: Demilitarization: