NSN 4320-00-178-9976

Rotary Pump - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4320-00-178-9976

| Mounting Type: |
|---|
| Frame |
| Intake Connection Quantity: |
| 1 |
| Intake Connection Type: |
| Oval flange |
| Discharge Connection Quantity: |
| 1 |
| Discharge Connection Type: |
| Oval flange |
| Drive Connection Type: |
| Spur gear |
| Media For Which Designed: |
| Oil |
| Maximum Discharge Flow Rate: |
| 46.0 gallons per minute |
| Discharge Pressure: |
| 50.0 pounds per square inch gage |
| Operating Speed At Rated Capacity: |
| 2000.0 revolutions per minute |
| Pump Rotation Direction: |
| Clockwise |
| |
| Rotary Pump Design: |
| Rotary Pump Design: Gear |
| |
| Gear |
| Gear Operation Method: |
| Gear Operation Method: Powered |
| Gear Operation Method: Powered Drive Shaft Type: |
| Gear Operation Method: Powered Drive Shaft Type: Woodruff keyway |
| Gear Operation Method: Powered Drive Shaft Type: Woodruff keyway Shelf Life: |
| Gear Operation Method: Powered Drive Shaft Type: Woodruff keyway Shelf Life: N/a |
| Gear Operation Method: Powered Drive Shaft Type: Woodruff keyway Shelf Life: N/a |
| Gear Operation Method: Powered Drive Shaft Type: Woodruff keyway Shelf Life: N/a Unit Of Measure: |
| Gear Operation Method: Powered Drive Shaft Type: Woodruff keyway Shelf Life: N/a Unit Of Measure: Demilitarization: |