## NSN 4320-00-193-1782

Rotary Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-193-1782

Prime Mover Quantity:
1
Prime Mover Cooling Medium:
Air
Intake Connection Quantity:
1
Intake Connection Type:
Round flange
Discharge Connection Quantity:
1
Discharge Connection Type:
Rectangular flange
Current Type:
Ac
Media For Which Designed:
Hydrocarbon fuels and oils
Environmental Protection:
Dripproof
Pump Quantity:
1
Cooling Method:
Self ventilated
Maximum Discharge Flow Rate:
40.0 gallons per minute
Discharge Pressure:
3000.0 pounds per square inch gage
Operating Speed At Rated Capacity:
1750.0 revolutions per minute
Pumping Element Operating Position:
Vertical
Rotary Pump Design:
Screw
Prime Mover Type:
Electric motor
Inclosure Type:
Partially enclosed
Current Rating In Amps:
120.0
Prime Mover Power Rating:
100.000 horsepower
Voltage In Volts:
440.0

## NSN 4320-00-193-1782

Rotary Pump Unit - Page 2 of 2



Three

Frequency In Hertz:

60.0

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A19400