# NSN 4320-00-194-3317

Centrifugal Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-194-3317

Prime Mover Quantity:
1
Mounting Type:
Base
Stage Quantity:
1
Intake Connection Quantity:
1
Intake Connection Type:
Round flange
Discharge Connection Quantity:
1
Discharge Connection Type:
Round flange
Current Type:
Ac
Media For Which Designed:
Hydrocarbon fuels and oils
Environmental Protection:
Dust-ignition proof
Pump Quantity:
1
Maximum Discharge Flow Rate:
875.0 gallons per minute
Total Head:
462.000 feet
Operating Speed At Rated Capacity:
3600.0 revolutions per minute
Pumping Element Operating Position:
Horizontal
Centrifugal Pump Design:
Radial flow
Centrifugal Pump Impeller Quantity:
1
Centrifugal Pump Impeller Suction Type:
Double
Prime Mover Type:
Electric motor
Inclosure Type:
Fully enclosed
Features Provided:
Self-priming

## NSN 4320-00-194-3317

Centrifugal Pump Unit - Page 2 of 2



**Prime Mover Power Rating:** 

150.000 horsepower

## Voltage In Volts:

440.0

Phase:

Three

## Frequency In Hertz:

60.0

#### **Reference Number Differentiating Characteristics:**

As differentiated by w/electric motor

Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

Yes - demil/mli

#### Fiig:

A19400