

View Online at <https://aerobasegroup.com/nsn/4320-00-195-4914>

Mounting Type:

Wheel

Discharge Connection Flange Thickness:

0.375 inches

Prime Mover Horsepower Rating:

36.000

Prime Mover Type:

Gasoline engine

Discharge Connection Type:

Flanged

Capacity Rating:

350.0 gallons per minute

Suction Connection Type:

Flanged

Pump Type:

Centrifugal

Suction Connection Flange Type:

Drilled

Suction Connection Flange Thickness:

0.375 inches

Suction Connection Flange Bolt Circle Diameter:

5.875 inches

Suction Connection Flange Bolt Hole Quantity:

8

Suction Connection Flange Bolt Hole Diameter:

0.438 inches

Discharge Connection Flange Bolt Circle Diameter:

5.875 inches

Discharge Connection Flange Bolt Hole Quantity:

8

Discharge Connection Flange Bolt Hole Diameter:

0.438 inches

Explosion Proof Feature:

Not included

Discharge Connection Flange Type:

Drilled

Ground Cable:

Included

Cable Reel:

Not included

Water Remover Type:

Strainer

Drum Emptying Manifold Assembly:

Not included

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T103-m