

View Online at <https://aerobasegroup.com/nsn/4320-00-196-5803>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air and water, fresh

**Stage Quantity:**

1

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Threaded internal

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Threaded external

**Current Type:**

Ac

**Media For Which Designed:**

Water, fresh

**Environmental Protection:**

Submersible

**Pump Quantity:**

1

**Cooling Method:**

Water-air cooled

**Maximum Discharge Flow Rate:**

5.0 gallons per minute

**Discharge Pressure:**

5.1 pounds per square inch gage

**Pumping Element Operating Position:**

Horizontal

**Centrifugal Pump Design:**

Mixed flow

**Centrifugal Pump Impeller Quantity:**

1

**Centrifugal Pump Impeller Suction Type:**

Single

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Current Rating In Amps:**

1.7

**Discharge Connection Thread Size And Series/type Designator:**

0.250-18 npt

**Intake Connection Thread Size And Series/type Designator:**

0.375-18 npt

**Prime Mover Power Rating:**

0.025 horsepower

**Voltage In Volts:**

115.0

**Phase:**

Single

**Special Features:**

Furnished with filter screen

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A19400