

View Online at <https://aerobasegroup.com/nsn/4320-00-196-5803>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air and water, fresh

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded external

Current Type:

Ac

Media For Which Designed:

Water, fresh

Environmental Protection:

Submersible

Pump Quantity:

1

Cooling Method:

Water-air cooled

Maximum Discharge Flow Rate:

5.0 gallons per minute

Discharge Pressure:

5.1 pounds per square inch gage

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Design:

Mixed flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

1.7

Discharge Connection Thread Size And Series/type Designator:

0.250-18 npt

Intake Connection Thread Size And Series/type Designator:

0.375-18 npt

Prime Mover Power Rating:

0.025 horsepower

Voltage In Volts:

115.0

Phase:

Single

Special Features:

Furnished with filter screen

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400