

View Online at <https://aerobasegroup.com/nsn/4320-00-197-5126>

Prime Mover Quantity:

1

Mounting Type:

Base

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Ac

Media For Which Designed:

Hydrocarbon fuels and oils

Pump Quantity:

1

Maximum Discharge Flow Rate:

19.2 gallons per minute

Discharge Pressure:

70.0 pounds per square inch gage

Operating Speed At Rated Capacity:

11500.0 revolutions per minute

Centrifugal Pump Design:

Radial flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Operation Relationship Design:

Independent

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

7.0

Discharge Connection Thread Size And Series/type Designator:

1.313-12 un

Intake Connection Thread Size And Series/type Designator:

1.313-12 un

Prime Mover Power Rating:

1.500 horsepower

Voltage In Volts:

115.0 and 200.0

Phase:

Three

Frequency In Hertz:

400.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A19400