NSN 4320-00-202-5846

Rotary Pump - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-202-5846

| M. C. T. |
|---|
| Mounting Type: |
| Base |
| Intake Connection Quantity: |
| 1 |
| Intake Connection Type: |
| Round flange |
| Discharge Connection Quantity: |
| 1 |
| Discharge Connection Type: |
| Round flange |
| Drive Connection Type: |
| Gear |
| Media For Which Designed: |
| Hydrocarbon fuels and oils |
| Maximum Discharge Flow Rate: |
| 34.0 gallons per minute and 2.0 gallons per minute |
| Discharge Pressure: |
| 600.0 pounds per square inch gage and 50.0 pounds per square inch gage |
| Operating Speed At Rated Capacity: |
| 3600.0 revolutions per minute and 300.0 revolutions per minute |
| Pumping Element Operating Position: |
| |
| Horizontal |
| Horizontal Pump Rotation Direction: |
| |
| Pump Rotation Direction: |
| Pump Rotation Direction: Counterclockwise |
| Pump Rotation Direction: Counterclockwise Volume Control Type: |
| Pump Rotation Direction: Counterclockwise Volume Control Type: Rotary |
| Pump Rotation Direction: Counterclockwise Volume Control Type: Rotary Rotary Pump Design: |
| Pump Rotation Direction: Counterclockwise Volume Control Type: Rotary Rotary Pump Design: Gear |
| Pump Rotation Direction: Counterclockwise Volume Control Type: Rotary Rotary Pump Design: Gear Operation Method: |
| Pump Rotation Direction: Counterclockwise Volume Control Type: Rotary Rotary Pump Design: Gear Operation Method: Powered |
| Pump Rotation Direction: Counterclockwise Volume Control Type: Rotary Rotary Pump Design: Gear Operation Method: Powered Drive Shaft Type: |
| Pump Rotation Direction: Counterclockwise Volume Control Type: Rotary Rotary Pump Design: Gear Operation Method: Powered Drive Shaft Type: Splined, straight external |
| Pump Rotation Direction: Counterclockwise Volume Control Type: Rotary Rotary Pump Design: Gear Operation Method: Powered Drive Shaft Type: Splined, straight external Drive Shaft End Diameter: |
| Pump Rotation Direction: Counterclockwise Volume Control Type: Rotary Rotary Pump Design: Gear Operation Method: Powered Drive Shaft Type: Splined, straight external Drive Shaft End Diameter: Between 0.863 inches and 0.867 inches |
| Pump Rotation Direction: Counterclockwise Volume Control Type: Rotary Rotary Pump Design: Gear Operation Method: Powered Drive Shaft Type: Splined, straight external Drive Shaft End Diameter: Between 0.863 inches and 0.867 inches Drive Shaft Length: |
| Pump Rotation Direction: Counterclockwise Volume Control Type: Rotary Rotary Pump Design: Gear Operation Method: Powered Drive Shaft Type: Splined, straight external Drive Shaft End Diameter: Between 0.863 inches and 0.867 inches Drive Shaft Length: Between 1.493 inches and 1.613 inches |
| Pump Rotation Direction: Counterclockwise Volume Control Type: Rotary Rotary Pump Design: Gear Operation Method: Powered Drive Shaft Type: Splined, straight external Drive Shaft End Diameter: Between 0.863 inches and 0.867 inches Drive Shaft Length: Between 1.493 inches and 1.613 inches Shelf Life: |
| Pump Rotation Direction: Counterclockwise Volume Control Type: Rotary Rotary Pump Design: Gear Operation Method: Powered Drive Shaft Type: Splined, straight external Drive Shaft End Diameter: Between 0.863 inches and 0.867 inches Drive Shaft Length: Between 1.493 inches and 1.613 inches Shelf Life: N/a |

No

NSN 4320-00-202-5846

Rotary Pump - Page 2 of 2



Fiig:

A19400