

View Online at <https://aerobasegroup.com/nsn/4320-00-202-9084>

**Prime Mover Quantity:**

1

**Mounting Type:**

Base

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Threaded internal

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Threaded internal

**Current Type:**

Dc

**Media For Which Designed:**

Oil

**Environmental Protection:**

Dust-ignition proof

**Pump Quantity:**

1

**Maximum Discharge Flow Rate:**

13.3 gallons per minute

**Discharge Pressure:**

10.0 pounds per square inch gage

**Operating Speed At Rated Capacity:**

2500.0 revolutions per minute

**Pumping Element Operating Position:**

Vertical

**Rotary Pump Design:**

Vane

**Operation Relationship Design:**

Simultaneous

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Discharge Connection Thread Size And Series/type Designator:**

1.000-11-1/2 npt

**Intake Connection Thread Size And Series/type Designator:**

1.000-11-1/2 npt

**Prime Mover Power Rating:**

0.250 horsepower

**Voltage In Volts:**

24.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A19400