NSN 4320-00-203-6613

Rotary Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-203-6613

B
Prime Mover Quantity:
1 Manualina Tamas
Mounting Type:
Base
Intake Connection Quantity:
1
Intake Connection Type:
Threaded internal
Discharge Connection Quantity:
1
Discharge Connection Type:
Threaded internal
Current Type:
Dc
Media For Which Designed:
Hydrocarbon fuels and oils
Environmental Protection:
Explosion proof
Pump Quantity:
1
Cooling Method:
Self ventilated
Discharge Pressure:
1250.0 pounds per square inch gage
Operating Speed At Rated Capacity:
1200.0 revolutions per minute
Pumping Element Operating Position:
Horizontal
Rotary Pump Design:
Gear
Operation Relationship Design:
Simultaneous
Prime Mover Type:
Electric motor
Inclosure Type:
Fully enclosed
Discharge Connection Thread Size And Series/type Designator:
0.750&14 npt
Intake Connection Thread Size And Series/type Designator:
0.750&14 npt
Prime Mover Power Rating:
3.500 horsepower

NSN 4320-00-203-6613

Rotary Pump Unit - Page 2 of 2



Vم	ltage	In \	/ol	lts:
vu	ııaue		<i>,</i> 0	ILO.

24.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400