

View Online at <https://aerobasegroup.com/nsn/4320-00-203-9859>

**Prime Mover Quantity:**

1

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Threaded internal

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Threaded internal

**Current Type:**

Dc

**Media For Which Designed:**

Alcohol and water, fresh

**Environmental Protection:**

Explosion proof

**Pump Quantity:**

1

**Cooling Method:**

Self ventilated

**Maximum Discharge Flow Rate:**

0.066 gallons per minute

**Discharge Pressure:**

15.0 pounds per square inch gage

**Operating Speed At Rated Capacity:**

12000.0 revolutions per minute

**Pumping Element Operating Position:**

Horizontal

**Volume Control Type:**

Rotary

**Control Location:**

Right side

**Rotary Pump Design:**

Vane

**Operation Relationship Design:**

Simultaneous

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Current Rating In Amps:**

1.8

**Discharge Connection Thread Size And Series/type Designator:**

0.438-20 unf

**Intake Connection Thread Size And Series/type Designator:**

0.438-20 unf

**Prime Mover Power Rating:**

0.010 horsepower

**Voltage In Volts:**

27.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A19400