

View Online at <https://aerobasegroup.com/nsn/4320-00-203-9866>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Threaded internal

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Threaded internal

**Current Type:**

Dc

**Media For Which Designed:**

Hydrocarbon fuels and oils

**Environmental Protection:**

Dust-ignition proof

**Pump Quantity:**

1

**Maximum Discharge Flow Rate:**

0.1 gallons per minute

**Discharge Pressure:**

30.0 pounds per square inch gage

**Pumping Element Operating Position:**

Horizontal

**Rotary Pump Design:**

Vane

**Operation Relationship Design:**

Simultaneous

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Discharge Connection Thread Size And Series/type Designator:**

0.438-20 unf

**Intake Connection Thread Size And Series/type Designator:**

0.438-20 unf

**Prime Mover Power Rating:**

0.013 horsepower

**Voltage In Volts:**

28.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A19400