

View Online at <https://aerobasegroup.com/nsn/4320-00-204-2091>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air and oil and water, fresh

**Stage Quantity:**

1

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Threaded internal

**Current Type:**

Ac

**Media For Which Designed:**

Water, fresh

**Environmental Protection:**

Submersible

**Pump Quantity:**

1

**Cooling Method:**

Water-air cooled

**Maximum Discharge Flow Rate:**

54.2 gallons per minute

**Discharge Pressure:**

9.9 pounds per square inch gage

**Total Head:**

5.000 feet

**Operating Speed At Rated Capacity:**

1500.0 revolutions per minute

**Pumping Element Operating Position:**

Vertical

**Centrifugal Pump Design:**

Radial flow

**Centrifugal Pump Impeller Quantity:**

1

**Centrifugal Pump Impeller Suction Type:**

Single

**Operation Relationship Design:**

Simultaneous

**Unpackaged Unit Length:**

8.500 inches

**Unpackaged Unit Width:**

7.5000 inches

**Unpackaged Unit Height:**

6.000 inches

**Pump Basic Material:**

Bronze

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Current Rating In Amps:**

9.6

**Discharge Connection Thread Size And Series/type Designator:**

1.250-11-1/2 npt

**Features Provided:**

Self-priming

**Prime Mover Power Rating:**

0.33 horsepower

**Voltage In Volts:**

115.0

**Phase:**

Single

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A19400