

View Online at <https://aerobasegroup.com/nsn/4320-00-204-4410>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Ac

Media For Which Designed:

Hydrocarbon fuels and oils

Environmental Protection:

Splash proof

Pump Quantity:

1

Cooling Method:

Air to air cooled

Maximum Discharge Flow Rate:

6.0 gallons per minute

Discharge Pressure:

150.0 pounds per square inch gage

Operating Speed At Rated Capacity:

11300.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Design:

Radial flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

7.0 and 4.2

Discharge Connection Thread Size And Series/type Designator:

0.875-14 unjf

Intake Connection Thread Size And Series/type Designator:

1.062-12 unj

Features Provided:

Self-priming

Prime Mover Power Rating:

2.000 horsepower

Voltage In Volts:

120.0 and 208.0

Phase:

Three

Frequency In Hertz:

380.0 and 420.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400