## NSN 4320-00-212-8989

Hydraulic Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-212-8989

Thread Direction:
Right-hand and right-hand
Mounting Type:
Flange
Keyway Width:
0.188 inches
Keyway Depth:
0.094 inches
Mounting Hole Diameter:
0.438 inches
Mounting Hole Quantity:
2
Thread Size:
0.500-14 and 0.500-14
Shaft Diameter:
0.625 inches
Operating Speed At Rated Capacity In Rpm:
3000.0
Mounting Bolt Circle Diameter:
4.188 inches
Keyway Length:
1.250 inches
Drive Shaft Type:
Machine keyway
Housing Material:
Iron, cast
Screw Thread Series Designator:
Nptf and nptf
Shaft Rotation Direction:
Clockwise and counterclockwise
Thread Location:
Internal and internal
Shaft Protrusion Length:
2.250 inches
Connection Quantity:
1 and 1
Connection Type:
Outlet
Maximum Working Pressure Rating At Specificationified Tempurature Range:
1200 psi at plus 50 degrees f to plus 150 degrees f
Connection Design:

Threaded and threaded

## **NSN 4320-00-212-8989** Hydraulic Motor - Page 2 of 2



Displacement Type:	
Constant	
Constant Displacement Per Revolution:	
0.714 cubic inches	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	

Fiig: T103-f