NSN 4320-00-223-4715

Rotary Pump - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-223-4715

| Mounting Type: |
|--|
| Frame |
| Intake Connection Quantity: |
| 1 |
| Intake Connection Type: |
| Threaded internal |
| Discharge Connection Quantity: |
| 1 |
| Discharge Connection Type: |
| Threaded internal |
| Drive Connection Type: |
| Rigid coupled |
| Media For Which Designed: |
| Hydrocarbon fuels and oils |
| Maximum Discharge Flow Rate: |
| 5.5 gallons per minute |
| Discharge Pressure: |
| 550.0 pounds per square inch gage |
| Operating Speed At Rated Capacity: |
| 1300.0 revolutions per minute |
| Pumping Element Operating Position: |
| Horizontal |
| Pump Rotation Direction: |
| Clockwise |
| Volume Control Type: |
| Rotary |
| Control Location: |
| Center |
| Rotary Pump Design: |
| Gear |
| Operation Method: |
| Powered |
| Drive Shaft Type: |
| Machine keyway |
| Drive Shaft End Diameter: |
| 0.997 inches |
| Drive Shaft Length: |
| 2.063 inches |
| Discharge Connection Thread Size And Series/type Designator: |
| 0.750-14 npt |
| Intake Connection Thread Size And Series/type Designator: |

0.750-14 npt

NSN 4320-00-223-4715

Rotary Pump - Page 2 of 2



| _ | | | • | | |
|---|---|----|---|----|----|
| • | n | ο. | • | 18 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400