## NSN 4320-00-224-8660

Centrifugal Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-224-8660

Prime Mover Quantity:
1
Prime Mover Cooling Medium:
Air
Mounting Type:
Base
Stage Quantity:
1
Intake Connection Quantity:
2
Intake Connection Type:
Round flange
Discharge Connection Quantity:
2
Discharge Connection Type:
Round flange
Current Type:
Ac
Media For Which Designed:
Brine
Environmental Protection:
Splash proof
Pump Quantity:
2
Cooling Method:
Blower cooled
Maximum Discharge Flow Rate:
70.0 gallons per minute and 30.0 gallons per minute
Total Head:
40.000 feet and 27.000 feet
Operating Speed At Rated Capacity:
1150.0 revolutions per minute
Pumping Element Operating Position:
Horizontal
Centrifugal Pump Design:
Radial flow
Centrifugal Pump Impeller Quantity:
2
Centrifugal Pump Impeller Suction Type:
Single
Operation Relationship Design:

Simultaneous

## NSN 4320-00-224-8660

Centrifugal Pump Unit - Page 2 of 2



Prime Mover Type:
Electric motor
Inclosure Type:
Fully enclosed
Current Rating In Amps:
7.5
Features Provided:
Self-priming
Voltage In Volts:
440.0
Phase:
Three
Frequency In Hertz:
60.0
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:

A19400