

View Online at <https://aerobasegroup.com/nsn/4320-00-237-3695>

Thread Direction:

Right-hand and right-hand

Torque Load Rating:

1200.0 inch-pounds

Mounting Type:

Flange

Mounting Hole Diameter:

0.375 inches

Mounting Hole Quantity:

4

Thread Size:

0.875-14 and 0.875-14

Shaft Diameter:

1.000 inches

Operating Speed At Rated Capacity In Rpm:

320.0

Mounting Bolt Circle Diameter:

3.250 inches

Drive Shaft Type:

Woodruff keyway

Housing Material:

Iron

Screw Thread Series Designator:

Nptf and nptf

Shaft Rotation Direction:

Clockwise and counterclockwise

Distance From End To Keyway Center:

0.730 inches

Thread Location:

Internal and internal

Shaft Protrusion Length:

1.780 inches

Connection Quantity:

1 and 1

Connection Type:

Inlet and outlet

Maximum Working Pressure Rating At Specificationified Temperature Range:

1750psi at minus 65 degrees f to @plus 165 degrees f

Connection Design:

Threaded and threaded

Sae Key Size Accommodated:

15

Displacement Type:

Constant or variable

Constant Displacement Per Revolution:

10.300 cubic inches

Mounting Bolt Hole Spacing:

45 degrees apart

Housing Surface Treatment:

Primer, mil-p-52192 and painted, mil-e-52227, color x24087

Special Features:

Mtg holes 3/8-16 unc thd

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T103-f