NSN 4320-00-251-6099

Centrifugal Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-251-6099

| Prime Mover Quantity: |
|---|
| 1 |
| Prime Mover Cooling Medium: |
| Air |
| Stage Quantity: |
| 1 |
| Discharge Connection Quantity: |
| 1 |
| Discharge Connection Type: |
| Threaded internal |
| Current Type: |
| Ac |
| Media For Which Designed: |
| Liquid |
| Environmental Protection: |
| Waterproof |
| Pump Quantity: |
| 1 |
| Cooling Method: |
| Self ventilated |
| Maximum Discharge Flow Rate: |
| 90.0 gallons per minute |
| Total Head: |
| 5.000 feet |
| Operating Speed At Rated Capacity: |
| 1725.0 revolutions per minute |
| Pumping Element Operating Position: |
| Vertical |
| Centrifugal Pump Design: |
| Mixed flow |
| Centrifugal Pump Impeller Quantity: |
| 1 |
| Centrifugal Pump Impeller Suction Type: |
| Single |
| Unpackaged Unit Width: |
| 10.7500 inches |
| Unpackaged Unit Height: |
| 10.500 inches |
| Pump Basic Material: |
| Plastic |
| Prime Mover Type: |
| Electric motor |

NSN 4320-00-251-6099Centrifugal Pump Unit - Page 2 of 2



| nclosure Type: |
|--|
| Fully enclosed |
| Current Rating In Amps: |
| 3.2 |
| Discharge Connection Thread Size And Series/type Designator: |
| 1.500-11-1/2 npt |
| Features Provided: |
| Self-priming |
| Prime Mover Power Rating: |
| 0.5 horsepower |
| Voltage In Volts: |
| 115.0 |
| Phase: |
| Single |
| Frequency In Hertz: |
| 60.0 |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| . |
| Demilitarization: |
| No |
| Fiig: |
| A19400 |
| |