

View Online at <https://aerobasegroup.com/nsn/4320-00-258-2695>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Stage Quantity:**

1

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Flared tube

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Threaded internal

**Current Type:**

Ac

**Media For Which Designed:**

Ethylene glycol

**Environmental Protection:**

Dust-ignition proof

**Pump Quantity:**

1

**Cooling Method:**

Blower cooled

**Maximum Discharge Flow Rate:**

1.4 gallons per minute

**Discharge Pressure:**

50.0 pounds per square inch gage

**Pumping Element Operating Position:**

Horizontal

**Centrifugal Pump Design:**

Radial flow

**Centrifugal Pump Impeller Quantity:**

1

**Centrifugal Pump Impeller Suction Type:**

Single

**Volume Control Type:**

Pressure compensation

**Control Location:**

Left side

**Operation Relationship Design:**

Simultaneous

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Current Rating In Amps:**

1.0 and 0.7

**Discharge Connection Thread Size And Series/type Designator:**

0.562-18 unjf

**Intake Connection Thread Size And Series/type Designator:**

0.562-18 unjf

**Features Provided:**

Self-priming

**Prime Mover Power Rating:**

0.250 horsepower

**Voltage In Volts:**

115.0 and 200.0

**Phase:**

Three

**Frequency In Hertz:**

400.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A19400