

View Online at <https://aerobasegroup.com/nsn/4320-00-258-2695>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Flared tube

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Ac

Media For Which Designed:

Ethylene glycol

Environmental Protection:

Dust-ignition proof

Pump Quantity:

1

Cooling Method:

Blower cooled

Maximum Discharge Flow Rate:

1.4 gallons per minute

Discharge Pressure:

50.0 pounds per square inch gage

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Design:

Radial flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Volume Control Type:

Pressure compensation

Control Location:

Left side

Operation Relationship Design:

Simultaneous

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

1.0 and 0.7

Discharge Connection Thread Size And Series/type Designator:

0.562-18 unjf

Intake Connection Thread Size And Series/type Designator:

0.562-18 unjf

Features Provided:

Self-priming

Prime Mover Power Rating:

0.250 horsepower

Voltage In Volts:

115.0 and 200.0

Phase:

Three

Frequency In Hertz:

400.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400