

View Online at <https://aerobasegroup.com/nsn/4320-00-267-1082>

Prime Mover Quantity:

1

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Round flange

Discharge Connection Quantity:

1

Discharge Connection Type:

Round flange

Current Type:

Dc

Media For Which Designed:

Water, fresh

Environmental Protection:

Drip-proof

Pump Quantity:

1

Maximum Discharge Flow Rate:

30.0 gallons per minute

Discharge Pressure:

23.7 pounds per square inch gage

Total Head:

51.000 feet

Operating Speed At Rated Capacity:

3500.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Design:

Radial flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Prime Mover Type:

Electric motor

Inclosure Type:

Partially enclosed

Current Rating In Amps:

10.0

Prime Mover Power Rating:

1.100 horsepower

Voltage In Volts:

115.0

Reference Number Differentiating Characteristics:

As differentiated by w/115 volt motor

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400