

View Online at <https://aerobasegroup.com/nsn/4320-00-267-3069>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Mounting Type:**

Base

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Round flange

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Round flange

**Current Type:**

Ac

**Media For Which Designed:**

Oil

**Environmental Protection:**

Splashtight

**Pump Quantity:**

1

**Cooling Method:**

Self ventilated

**Maximum Discharge Flow Rate:**

5.0 gallons per minute

**Discharge Pressure:**

25.0 pounds per square inch gage

**Operating Speed At Rated Capacity:**

680.0 revolutions per minute

**Pumping Element Operating Position:**

Horizontal

**Rotary Pump Design:**

Gear

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Current Rating In Amps:**

1.4

**Prime Mover Power Rating:**

0.750 horsepower

**Voltage In Volts:**

440.0

**Phase:**

Three

**Frequency In Hertz:**

60.0

**Reference Number Differentiating Characteristics:**

As differentiated by century electric co, motor, w/controller

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A19400