## NSN 4320-00-267-3163

Centrifugal Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-267-3163

| Prime Mover Quantity:                   |
|---|
| 1                                       |
| Prime Mover Cooling Medium:             |
| Air                                     |
| Mounting Type:                          |
| Base                                    |
| Stage Quantity:                         |
| 2                                       |
| Intake Connection Quantity:             |
| 1                                       |
| Intake Connection Type:                 |
| Round flange                            |
| Discharge Connection Quantity:          |
| 1                                       |
| Discharge Connection Type:              |
| Round flange                            |
| Current Type:                           |
| Ac                                      |
| Media For Which Designed:               |
| Water, salt                             |
| Environmental Protection:               |
| Dripproof                               |
| Pump Quantity:                          |
| 1                                       |
| Cooling Method:                         |
| Self ventilated                         |
| Maximum Discharge Flow Rate:            |
| 200.0 gallons per minute                |
| Total Head:                             |
| 224.000 feet                            |
| Operating Speed At Rated Capacity:      |
| 1750.0 revolutions per minute           |
| Pumping Element Operating Position:     |
| Horizontal                              |
| Centrifugal Pump Design:                |
| Radial flow                             |
| Centrifugal Pump Impeller Quantity:     |
| 2                                       |
| Centrifugal Pump Impeller Suction Type: |
| Single                                  |
| Prime Mover Type:                       |
| Electric motor                          |

## **NSN 4320-00-267-3163**Centrifugal Pump Unit - Page 2 of 2



| Inclosure Type:                                   |
|---|
| Partially enclosed                                |
| Current Rating In Amps:                           |
| 30.0  |
| Voltage In Volts:                                 |
| 440.0   |
| Phase:  |
| Three   |
| Special Features:                                 |
| Provided w/controller                             |
| Frequency In Hertz:                               |
| 60.0  |
| Reference Number Differentiating Characteristics: |
| As differentiated by cw rotation                  |
| Shelf Life:                                       |
| N/a   |
| Unit Of Measure:                                  |
|   |
| Demilitarization:                                 |
| No  |
| Fiig:   |
| A19400  |