NSN 4320-00-267-3195

Centrifugal Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-267-3195

Prime Mover Quantity:

Prime Mover Quantity:
1
Prime Mover Cooling Medium:
Air
Stage Quantity:
6
Intake Connection Quantity:
1
Intake Connection Type:
Round flange
Discharge Connection Quantity:
1
Discharge Connection Type:
Round flange
Current Type:
Dc
Media For Which Designed:
Water, salt
Environmental Protection:
Dripproof
Pump Quantity:
1
1 Cooling Method:
·
Cooling Method:
Cooling Method: Self ventilated
Cooling Method: Self ventilated Maximum Discharge Flow Rate:
Cooling Method: Self ventilated Maximum Discharge Flow Rate: 80.0 gallons per minute
Cooling Method: Self ventilated Maximum Discharge Flow Rate: 80.0 gallons per minute Total Head:
Cooling Method: Self ventilated Maximum Discharge Flow Rate: 80.0 gallons per minute Total Head: 50.000 feet
Cooling Method: Self ventilated Maximum Discharge Flow Rate: 80.0 gallons per minute Total Head: 50.000 feet Suction Lift:
Cooling Method: Self ventilated Maximum Discharge Flow Rate: 80.0 gallons per minute Total Head: 50.000 feet Suction Lift: 20.000 feet
Cooling Method: Self ventilated Maximum Discharge Flow Rate: 80.0 gallons per minute Total Head: 50.000 feet Suction Lift: 20.000 feet Operating Speed At Rated Capacity:
Cooling Method: Self ventilated Maximum Discharge Flow Rate: 80.0 gallons per minute Total Head: 50.000 feet Suction Lift: 20.000 feet Operating Speed At Rated Capacity: 1100.0 revolutions per minute
Cooling Method: Self ventilated Maximum Discharge Flow Rate: 80.0 gallons per minute Total Head: 50.000 feet Suction Lift: 20.000 feet Operating Speed At Rated Capacity: 1100.0 revolutions per minute Pumping Element Operating Position:
Cooling Method: Self ventilated Maximum Discharge Flow Rate: 80.0 gallons per minute Total Head: 50.000 feet Suction Lift: 20.000 feet Operating Speed At Rated Capacity: 1100.0 revolutions per minute Pumping Element Operating Position: Vertical
Cooling Method: Self ventilated Maximum Discharge Flow Rate: 80.0 gallons per minute Total Head: 50.000 feet Suction Lift: 20.000 feet Operating Speed At Rated Capacity: 1100.0 revolutions per minute Pumping Element Operating Position: Vertical Centrifugal Pump Design:
Cooling Method: Self ventilated Maximum Discharge Flow Rate: 80.0 gallons per minute Total Head: 50.000 feet Suction Lift: 20.000 feet Operating Speed At Rated Capacity: 1100.0 revolutions per minute Pumping Element Operating Position: Vertical Centrifugal Pump Design: Radial flow
Cooling Method: Self ventilated Maximum Discharge Flow Rate: 80.0 gallons per minute Total Head: 50.000 feet Suction Lift: 20.000 feet Operating Speed At Rated Capacity: 1100.0 revolutions per minute Pumping Element Operating Position: Vertical Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity:
Cooling Method: Self ventilated Maximum Discharge Flow Rate: 80.0 gallons per minute Total Head: 50.000 feet Suction Lift: 20.000 feet Operating Speed At Rated Capacity: 1100.0 revolutions per minute Pumping Element Operating Position: Vertical Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity: 6
Cooling Method: Self ventilated Maximum Discharge Flow Rate: 80.0 gallons per minute Total Head: 50.000 feet Suction Lift: 20.000 feet Operating Speed At Rated Capacity: 1100.0 revolutions per minute Pumping Element Operating Position: Vertical Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity: 6 Centrifugal Pump Impeller Suction Type:

NSN 4320-00-267-3195

Centrifugal Pump Unit - Page 2 of 2



Inclosure Type:
Partially enclosed
Current Rating In Amps:
15.0
Voltage In Volts:
250.0
Reference Number Differentiating Characteristics:
Provided w/controller
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A19400