

View Online at <https://aerobasegroup.com/nsn/4320-00-267-3326>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Stage Quantity:**

1

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Round flange

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Round flange

**Current Type:**

Dc

**Media For Which Designed:**

Water, salt

**Environmental Protection:**

Dripproof

**Pump Quantity:**

1

**Cooling Method:**

Self ventilated

**Maximum Discharge Flow Rate:**

560.0 gallons per minute

**Discharge Pressure:**

12.6 pounds per square inch gage

**Total Head:**

28.000 feet

**Operating Speed At Rated Capacity:**

1700.0 revolutions per minute

**Pumping Element Operating Position:**

Vertical

**Centrifugal Pump Design:**

Radial flow

**Centrifugal Pump Impeller Quantity:**

1

**Centrifugal Pump Impeller Suction Type:**

Single

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Partially enclosed

**Current Rating In Amps:**

32.0

**Prime Mover Power Rating:**

8.500 horsepower

**Voltage In Volts:**

230.0

**Reference Number Differentiating Characteristics:**

W/o controller, ccw rotation

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A19400