

View Online at <https://aerobasegroup.com/nsn/4320-00-267-3326>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Round flange

Discharge Connection Quantity:

1

Discharge Connection Type:

Round flange

Current Type:

Dc

Media For Which Designed:

Water, salt

Environmental Protection:

Dripproof

Pump Quantity:

1

Cooling Method:

Self ventilated

Maximum Discharge Flow Rate:

560.0 gallons per minute

Discharge Pressure:

12.6 pounds per square inch gage

Total Head:

28.000 feet

Operating Speed At Rated Capacity:

1700.0 revolutions per minute

Pumping Element Operating Position:

Vertical

Centrifugal Pump Design:

Radial flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Prime Mover Type:

Electric motor

Inclosure Type:

Partially enclosed

Current Rating In Amps:

32.0

Prime Mover Power Rating:

8.500 horsepower

Voltage In Volts:

230.0

Reference Number Differentiating Characteristics:

W/o controller, ccw rotation

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400