

View Online at <https://aerobasegroup.com/nsn/4320-00-267-4495>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Round flange

Discharge Connection Quantity:

1

Discharge Connection Type:

Round flange

Current Type:

Dc

Media For Which Designed:

Water, fresh

Environmental Protection:

Dripproof

Pump Quantity:

1

Cooling Method:

Self ventilated

Maximum Discharge Flow Rate:

25.0 gallons per minute

Discharge Pressure:

3.6 pounds per square inch gage

Total Head:

51.000 feet

Operating Speed At Rated Capacity:

3500.0 revolutions per minute

Pumping Element Operating Position:

Vertical

Centrifugal Pump Design:

Radial flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Prime Mover Type:

Electric motor

Inclosure Type:

Partially enclosed

Current Rating In Amps:

10.0

Voltage In Volts:

115.0

Reference Number Differentiating Characteristics:

With 115 v dc motor and controller

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400