NSN 4320-00-277-1692

Centrifugal Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-277-1692

Prime Mover Quantity:
1
Prime Mover Cooling Medium:
Air
Stage Quantity:
1
Intake Connection Quantity:
1
Intake Connection Type:
Round flange
Discharge Connection Quantity:
1
Discharge Connection Type:
Round flange
Current Type:
Ac
Media For Which Designed:
Water, salt
Environmental Protection:
Splashtight
Pump Quantity:
1
Cooling Method:
Self ventilated
Maximum Discharge Flow Rate:
3.3 gallons per minute
Total Head:
43.500 feet
Operating Speed At Rated Capacity:
3500.0 revolutions per minute
Pumping Element Operating Position:
Vertical
Centrifugal Pump Design:
Radial flow
Centrifugal Pump Impeller Quantity:
1
Centrifugal Pump Impeller Suction Type:
Single
Prime Mover Type:
Electric motor
Inclosure Type:
Fully enclosed

NSN 4320-00-277-1692 Centrifugal Pump Unit - Page 2 of 2



Current Rating In Amps:
1.4
Voltage In Volts:
440.0
Phase:
Three
Frequency In Hertz:
60.0
Reference Number Differentiating Characteristics:
Furnished w/440 v ac motor and controller
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A19400