NSN 4320-00-288-9668

Centrifugal Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-288-9668

Prime Mover Quantity:
1
Prime Mover Cooling Medium:
Air
Stage Quantity:
2
Intake Connection Quantity:
1
Intake Connection Type:
Round flange
Discharge Connection Quantity:
1
Discharge Connection Type:
Round flange
Current Type:
Ac
Media For Which Designed:
Water, fresh
Environmental Protection:
Dripproof
Pump Quantity:
1
Cooling Method:
Self ventilated
Self ventilated Maximum Discharge Flow Rate:
Maximum Discharge Flow Rate:
Maximum Discharge Flow Rate: 75.0 gallons per minute
Maximum Discharge Flow Rate: 75.0 gallons per minute Total Head:
Maximum Discharge Flow Rate: 75.0 gallons per minute Total Head: 173.000 feet
Maximum Discharge Flow Rate: 75.0 gallons per minute Total Head: 173.000 feet Operating Speed At Rated Capacity:
Maximum Discharge Flow Rate: 75.0 gallons per minute Total Head: 173.000 feet Operating Speed At Rated Capacity: 1750.0 revolutions per minute
Maximum Discharge Flow Rate: 75.0 gallons per minute Total Head: 173.000 feet Operating Speed At Rated Capacity: 1750.0 revolutions per minute Pumping Element Operating Position:
Maximum Discharge Flow Rate: 75.0 gallons per minute Total Head: 173.000 feet Operating Speed At Rated Capacity: 1750.0 revolutions per minute Pumping Element Operating Position: Vertical
Maximum Discharge Flow Rate: 75.0 gallons per minute Total Head: 173.000 feet Operating Speed At Rated Capacity: 1750.0 revolutions per minute Pumping Element Operating Position: Vertical Centrifugal Pump Design:
Maximum Discharge Flow Rate: 75.0 gallons per minute Total Head: 173.000 feet Operating Speed At Rated Capacity: 1750.0 revolutions per minute Pumping Element Operating Position: Vertical Centrifugal Pump Design: Radial flow
Maximum Discharge Flow Rate: 75.0 gallons per minute Total Head: 173.000 feet Operating Speed At Rated Capacity: 1750.0 revolutions per minute Pumping Element Operating Position: Vertical Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity:
Maximum Discharge Flow Rate: 75.0 gallons per minute Total Head: 173.000 feet Operating Speed At Rated Capacity: 1750.0 revolutions per minute Pumping Element Operating Position: Vertical Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity: 2
Maximum Discharge Flow Rate: 75.0 gallons per minute Total Head: 173.000 feet Operating Speed At Rated Capacity: 1750.0 revolutions per minute Pumping Element Operating Position: Vertical Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity: 2 Centrifugal Pump Impeller Suction Type:
Maximum Discharge Flow Rate: 75.0 gallons per minute Total Head: 173.000 feet Operating Speed At Rated Capacity: 1750.0 revolutions per minute Pumping Element Operating Position: Vertical Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity: 2 Centrifugal Pump Impeller Suction Type: Single
Maximum Discharge Flow Rate: 75.0 gallons per minute Total Head: 173.000 feet Operating Speed At Rated Capacity: 1750.0 revolutions per minute Pumping Element Operating Position: Vertical Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity: 2 Centrifugal Pump Impeller Suction Type: Single Operation Relationship Design:

NSN 4320-00-288-9668

Centrifugal Pump Unit - Page 2 of 2



Inclosure Type:
Open
Current Rating In Amps:
10.0
Voltage In Volts:
440.0
Phase:
Three
Frequency In Hertz:
60.0
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A19400