NSN 4320-00-289-3673

Hydraulic Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-289-3673

Torque Load Rating:
360.0 inch-pounds
Mounting Type:
Flange
Keyway Width:
0.250 inches
Keyway Depth:
0.125 inches
Mounting Hole Diameter:
0.563 inches
Mounting Hole Quantity:
4
Shaft Diameter:
0.9997 inches
Bolt Hole Quantity:
4
Operating Speed At Rated Capacity In Rpm:
60.0
Keyway Length:
0.625 inches
Bolt Hole Diameter:
0.563 inches
Drive Shaft Type:
Machine keyway
Housing Material:
Bronze
Shaft Rotation Direction:
Clockwise
Shaft Protrusion Length:
7.094 inches
Connection Quantity:
1 and 1
Connection Type:
Inlet and outlet
Maximum Working Pressure Rating At Specificationified Tempurature Range:
1000 at no specified temp range
Connection Design:
Flanged and flanged
Displacement Type:
Constant
Constant Displacement Per Revolution:

5.750 cubic inches

NSN 4320-00-289-3673

Hydraulic Motor - Page 2 of 2



Bolt Hole Spacing:

2.250 in. By 3.000 in. C to $\ensuremath{\text{c}}$

Mounting Bolt Hole Spacing:

3 in. C to c

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

T103-f