

View Online at <https://aerobasegroup.com/nsn/4320-00-289-7977>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Mounting Type:**

Frame

**Stage Quantity:**

1

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Threaded internal

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Threaded internal

**Current Type:**

Ac

**Media For Which Designed:**

Water, fresh

**Environmental Protection:**

Waterproof

**Pump Quantity:**

1

**Cooling Method:**

Self ventilated

**Maximum Discharge Flow Rate:**

65.0 gallons per minute

**Total Head:**

50.000 feet

**Suction Lift:**

10.000 feet

**Operating Speed At Rated Capacity:**

3600.0 revolutions per minute

**Pumping Element Operating Position:**

Horizontal

**Centrifugal Pump Design:**

Radial flow

**Centrifugal Pump Impeller Quantity:**

1

**Centrifugal Pump Impeller Suction Type:**

Single

**Operation Relationship Design:**

Simultaneous

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Discharge Connection Thread Size And Series/type Designator:**

1.500-11-1/2 npt

**Intake Connection Thread Size And Series/type Designator:**

1.500-11-1/2 npt

**Features Provided:**

Self-priming

**Prime Mover Power Rating:**

2.0 horsepower

**Voltage In Volts:**

208.0

**Phase:**

Three

**Special Features:**

W/1 ea adapter, 4730002776844; w/1 ea adapter, 4730002788271; w/1 ea elbow, 4730002775636; w/1 ea nipple, 4730002027770; w/motor starter, magneto type, w/nema type 4 water tight enclosure, and start-stop push button in enclosure cover

**Frequency In Hertz:**

60.0

**Specification Or Standard:**

1 type

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A19400