NSN 4320-00-293-7333

Hydraulic Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-293-7333

Torque Load Rating:
500.0 inch-pounds
Mounting Type:
Flange
Mounting Hole Diameter:
0.500 inches
Mounting Hole Quantity:
8
Thread Size:
0.250-11-1 and 0.250-11-1 and 0.250-11-1
Shaft Diameter:
Between 1.9995 inches and 2.0000 inches
Operating Speed At Rated Capacity In Rpm:
1500.0
Drive Shaft Type:
Tongue
Housing Material:
Iron, cast
Screw Thread Series Designator:
Npt and npt and npt
Thread Location:
Internal and internal and internal
Shaft Protrusion Length:
Between 4.281 inches and 4.343 inches
Connection Type:
Outlet
Maximum Working Pressure Rating At Specificationified Tempurature Range:
2000 psi
Connection Design:
Threaded
Displacement Type:
Constant
Constant Displacement Per Revolution:
15.500 cubic inches
Mounting Bolt Hole Spacing:
30 degrees and 60 degrees alternate spacing on 5.500 in. Diameter bolt circle
Special Features:
1/2 in13 unc tapped mtg holes
Shelf Life:
N/a

NSN 4320-00-293-7333

Hydraulic Motor - Page 2 of 2



Demilitarization:

No

Fiig:

T103-f