NSN 4320-00-322-1510

Hydraulic Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-322-1510 **Thread Direction:** Right-hand and right-hand **Torque Load Rating:** 1766.0 inch-pounds **Mounting Type:** Flange **Mounting Hole Diameter:** 0.375 inches **Mounting Hole Quantity: Thread Size:** 0.500-14 and 0.500-14 **Shaft Diameter:** 1.000 inches **Operating Speed At Rated Capacity In Rpm:** 250.0 **Mounting Bolt Circle Diameter:** 3.250 inches **Drive Shaft Type:** Woodruff keyway **Screw Thread Series Designator:** Nptf and nptf **Shaft Rotation Direction:** Clockwise **Distance From End To Keyway Center:** 0.746 inches **Thread Location:** Internal and internal **Shaft Protrusion Length:** 1.700 inches **Connection Quantity: Connection Type:** Inlet and outlet **Maximum Working Pressure Rating At Specificationified Tempurature Range:** 1000psi at plus 30 degrees f to 275 degrees f **Connection Design:** Threaded and threaded Sae Key Size Accommodated:

Displacement Type:

Constant

NSN 4320-00-322-1510

Hydraulic Motor - Page 2 of 2



Constant	Displacement	Per Revolution:
JUHSLAHL	Displacement	rei nevolution.

14.900 cubic inches

Mounting Bolt Hole Spacing:

2.290 in. By 2.290 in.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T103-f